



6+ GHz Range Series			
		Point-to-Multipoint	Point-to-Point
		Multipoint 8260 Series	Edge Quickbridge® 1066 LNK
			
Frequency Band (Subject to country regulations)	<ul style="list-style-type: none"> 5.900 – 6.425 GHz 	<ul style="list-style-type: none"> 5.900 – 6.425 GHz 	<ul style="list-style-type: none"> 5.900 – 6.425 GHz
MIMO	<ul style="list-style-type: none"> 2x2:2 	<ul style="list-style-type: none"> 2x2:2 	<ul style="list-style-type: none"> 2x2:2
Channel Size	<ul style="list-style-type: none"> 40 MHz, 20 MHz, 10 MHz, 5 MHz channel bandwidth with 1 MHz channel spacing 	<ul style="list-style-type: none"> 40 MHz, 20 MHz, 10 MHz, 5 MHz channel bandwidth with 1 MHz channel spacing 	<ul style="list-style-type: none"> 40 MHz, 20 MHz, 10 MHz, 5 MHz channel bandwidth with 1 MHz channel spacing
Throughput	<ul style="list-style-type: none"> Up to 222 Mbps @ 40 MHz Up to 121 Mbps @ 20 MHz Up to 50 Mbps @ 10 MHz Up to 22 Mbps @ 5 MHz 	<ul style="list-style-type: none"> Up to 222 Mbps @ 40 MHz Up to 121 Mbps @ 20 MHz Up to 50 Mbps @ 10 MHz Up to 22 Mbps @ 5 MHz 	<ul style="list-style-type: none"> Up to 222 Mbps @ 40 MHz Up to 121 Mbps @ 20 MHz Up to 50 Mbps @ 10 MHz Up to 22 Mbps @ 5 MHz
TX Power	<ul style="list-style-type: none"> Up to 25 dBm (Dual chain) 	<ul style="list-style-type: none"> Up to 25 dBm (Dual chain) 	<ul style="list-style-type: none"> Up to 25 dBm (Dual chain)
Antenna	<ul style="list-style-type: none"> MP-8260-BSU or MP-8260-SUA: Two N-type connectors MP-8260-BS9: Integrated 2x2 MIMO 16dBi, 90°, dual polarized sector antenna 	<ul style="list-style-type: none"> Integrated 2x2 MIMO 15 dBi Dual Polarized 33 degree Panel Antenna 	<ul style="list-style-type: none"> Integrated 2x2 MIMO 15 dBi Dual Polarized 33 degree Panel Antenna
Management	<ul style="list-style-type: none"> Web GUI (admin, advanced, monitor), CLI, ProximVision Advanced 	<ul style="list-style-type: none"> Web GUI (admin, advanced, monitor), CLI, ProximVision Advanced 	<ul style="list-style-type: none"> Web GUI (admin, advanced, monitor), CLI, ProximVision Advanced
Security	<ul style="list-style-type: none"> AES - 128 bits Secure management (SSL/TLS, SSH, SNMPv3) Proprietary nature of RF protocol 	<ul style="list-style-type: none"> AES - 128 bits Secure management (SSL/TLS, SSH, SNMPv3) Proprietary nature of RF protocol 	<ul style="list-style-type: none"> AES - 128 bits Secure management (SSL/TLS, SSH, SNMPv3) Proprietary nature of RF protocol
Ethernet Ports	<ul style="list-style-type: none"> Two auto MDI-X RJ45 10/100/1000Mbps Ethernet (Port #1 with PoE in & Data, Port #2 with PoE out & Data) 	<ul style="list-style-type: none"> One auto MDI-X RJ45 10/100 Mbps Ethernet with PoE in 	<ul style="list-style-type: none"> One auto MDI-X RJ45 10/100 Mbps Ethernet with PoE in
QoS	<ul style="list-style-type: none"> Service flow based QoS with 32 queues and layer 2, 3 and 4 packet identification rules 	<ul style="list-style-type: none"> Service flow based QoS with 32 queues and layer 2, 3 and 4 packet identification rules 	<ul style="list-style-type: none"> Service flow based QoS with 32 queues and layer 2, 3 and 4 packet identification rules
Mobility	<ul style="list-style-type: none"> High speed roaming up to 185 mph 	<ul style="list-style-type: none"> High speed roaming up to 185 mph 	<ul style="list-style-type: none"> High speed roaming up to 185 mph
Humidity - IP Rating	<ul style="list-style-type: none"> 100% relative humidity - IP67 	<ul style="list-style-type: none"> 100% relative humidity - IP67 	<ul style="list-style-type: none"> 100% relative humidity - IP67
Operating Temperature	<ul style="list-style-type: none"> -40° to 60° C 	<ul style="list-style-type: none"> -30° to 55° C 	<ul style="list-style-type: none"> -30° to 55° C
Certifications			
Dimensions	<ul style="list-style-type: none"> MP-8260-BSU, SUA: 250 x 220 x 72 mm, 1.9 kg MP-8260-BS9: 370 x 370 x 107 mm, 3.3 kg 	<ul style="list-style-type: none"> MP-1060-CPE: 170 x 217 x 56 mm, 1.20 kg 	<ul style="list-style-type: none"> Dimensions: 126 x 219 x 65.5 mm, Weight: 0.950 kg
Product Models	<ul style="list-style-type: none"> MP-8260-BSU-WD MP-8260-BS9-WD MP-8260-SUA-WD 	<ul style="list-style-type: none"> MP-1060-CPE-WD 	<ul style="list-style-type: none"> QB-1066-LNK