

# ORiNOCO® QB-9100 Series

## Access Point with built-in Backhaul



## Proxim introduces the ORiNOCO® Quickbridge® 9100, the first wireless solution that combines a 2.4 GHz Access Point and 5 GHz Backhaul

ORiNOCO® Quickbridge® 9100 takes advantage of Proxim's expertise in both Wi-Fi and long haul point-to-point systems to deliver a 2.4 GHz 802.11n Access Point with a built-in 5 GHz high capacity backhaul solution.

With dual radio support, one for Wi-Fi and one for high capacity backhaul the, ORiNOCO® QB-9100 is ideal for Carriers who need wireless backhaul for their 3G/4G small cell and can have the backhaul and Wi-Fi offload in a single unit. ORiNOCO® QB-9100 also offers new capability to Video Protection or ITS network by providing operators with secure Wi-Fi access to information from the unit while in the field, on standard Wi-Fi devices.

ORiNOCO® Quickbridge® 9100 leverages the benefits of OFDM, MIMO radio innovations and Proxim's proprietary Wireless Outdoor Routing Protocol (WORP®) to provide wireless performance in excess of 4G or Wi-Fi based backhaul products today.

### World Class Performance

- 802.11b/g/n Wi-Fi certified Access Point that delivers 300 Mbps data rate
- Point-to-Point Backhaul that delivers 866 Mbps data rate at distances of over 5 miles (8 km)
- Very low latency of 2 to 3 ms to support voice and video applications over long distances
- Dual IPv4 and IPv6 stack for transparent evolution to tomorrow networks
- Built-in feature rich network protocols for bridging, routing and gateway functionality

### Highly Secure

- Implements AES encryption and Radius authentication for secure outdoor wireless communications
- Secure management (SSL/TLS1.2, SSH and SNMPv3) preventing unwanted configuration changes

### Advanced Features

- Features dual Gigabit Ethernet ports with PoE out to power other devices such as surveillance cameras or additional radios
- Supports Deep packet inspection to create unique and sophisticated service rules and tiered service classes with ease
- Compatibility with LACP switches for link aggregation
- Built in spectrum analyzer to scan frequency bands for interference, and select a channel appropriately

### Carrier-Grade Backhaul

- Features Ethernet ports with IEEE 1588v2 synchronization and support for Jumbo frames
- Public HotSpot integration with Home Page redirect and Walled Garden
- HotSpot 2.0 to automatically discover and seamlessly authenticate to public Wi-Fi networks

### Unparalleled Flexibility and Convenience with Centralized Management

- ProximVision® Advanced supports ORiNOCO® QB-9100 giving network architects unparalleled flexibility and control of the units
  - Rapid Network Deployment: Automates configuration processes for faster, more efficient deployment of Proxim Wireless networks
  - Advanced Configuration Capabilities: Gives network managers an option for exhaustive device configuration with a software-based tool
  - Greater Ease of Use and Upgradability: Supports a greater number of devices than competitively priced solutions and provides the simplest path to configuration and upgrade

PRODUCT MODELS					
QB-9100	ORINOCO® QB-9100, MIMO 2x2, 802.11g/n AP with link, 867 Mbps, MIMO 2x2, Type-N Connectors				
QB-9150	ORINOCO® QB-9150, MIMO 2x2, 802.11g/n AP with link, 867 Mbps, MIMO 2x2, 22 dBi panel				
INTERFACES					
WIRED ETHERNET	Two auto MDI-X RJ45 10/100/1000Mbps Ethernet - Port #1 with PoE in & Data		- Port #2 with PoE out & Data		
WIRELESS PROTOCOL	- Radio #1: WORP®		- Radio #2: 802.11b/g/n (Remote end only)		
RADIO					
	Radio #1			Radio #2 (Remote end only)	
FREQUENCY	5.150 – 5.925 GHz (Subject to Country Regulations)			2.400 – 2.484 (Subject to Country Regulations)	
				802.11n	802.11g
					802.11b
MIMO	2x2:2			2x2:2	N/A
MODULATION	OFDM BPSK - QAM256			OFDM BPSK - QAM64	OFDM BPSK-QAM64
DATA RATE	Up to 866 Mbps			Up to 300Mbps	Up to 54Mbps
	80 MHz	40 MHz	20 MHz	40 MHz	20 MHz
TX POWER	MCS0: 28	MCS0: 28	MCS0: 29	MCS0/8: 26	MCS0/8: 26
	MCS9: 21	MCS9: 22	MCS8: 25	MCS7/15: 20	MCS7/15: 21
RX SENSITIVITY (BER=10 <sup>-6</sup> )	MCS0: -89	MCS0: -93	MCS0: -94	MCS0/8: -88/90	MCS0/8: -92/91
	MCS9: -68	MCS9: -71	MCS8: -74	MCS7/15: -72/69	MCS7/15: -74/72
OTHER	Dynamic Channel Selection (DCS) based on interference detection Dynamic Frequency Selection (DFS) based on radar signature Automatic Transmit Power Control (ATPC) with EIRP limit support			Automatic Channel Selection (ACS)	
ANTENNA					
	Radio #1			Radio #2 (Remote end only)	
QB-9100	Two N-type Connectors with built-in Surge Protection			Two N-type Connectors with built-in Surge Protection	
QB-9150	Integrated 2x2 MIMO 22dBi Dual Polarized 1 foot Panel Antenna			Two N-type Connectors with built-in Surge Protection	
SECURITY					
	Radio #1			Radio #2 (Remote end only)	
ENCRYPTION	AES 128			802.11i/WPA2 and WPA Wireless Security with AES-128, TKIP or WEP	
AUTHENTICATION	Internal MAC Address Control List, Radius based Authentication			Enterprise/802.1x, Personal/ PSK (Pre Shared Key) or Open	
802.1X SUPPORT				PEAP, LEAP, EAP-FAST, EAP-SIM, EAP-TTLS, EAP-AKA	
QOS					
	Radio #1			Radio #2 (Remote end only)	
	Asymmetric UL/DL CIR (committed) and MIR (maximum) information rate per service flow with Best Effort and Real Time Polling Services			802.11e/WMM Enhanced Distributed Channel Access, 4 priority queues	
Packet Classification Capabilities	802.1p priority, IPTOS, VLAN ID, IP addresses, ports, Ethernet addresses, IP protocol, and EtherType			802.1p priority, IPTOS	
THROUGHPUT					
	Radio #1			Radio #2 (Remote end only)	
	Up to 633 Mbps @ 80 MHz			Up to 150 Mbps	
MANAGEMENT					
REMOTE	Telnet and SSH, Web GUI and SSL, TFTP, SNMPv3				
SNMP	SNMP v1-v2c-v3, RFC-1213, RFC-1215, RFC-2790, RFC-2571, RFC-3412, RFC-3414, Private MIB				
OTHER	Syslog, sFlow™ agent, SNMP and local time, Spectrum analyzer				
SYNCHRONIZATION					
	IEEE 1588v2 Ethernet Synchronization				
NETWORK					
	Radio #1			Radio #2 (Remote end only)	
MODES	Bridging (support LACP through external switches), Routing (RIP v2 and IP tunneling)			Access Point	
IP STACK	IPv4 and IPv6 simultaneously				
GATEWAY FEATURES	DHCP Server & relay, NAT with Std ALGs				
VLAN	802.1Q: Management VLAN, Transparent, Access, Trunk and Mixed mode. QinQ double tagging				
POWER					
	INPUT			OUTPUT	
	36 to 57 VDC via Ethernet port1 (Power over Ethernet) (PoE) 12 VDC via Access port Power should not be provided simultaneously on both ports.			48 to 57 VDC – 25 Watt max on Ethernet port2 (PoE – software controlled) 12 VDC on Access port	
POWER CONSUMPTION					
	Local end: 14 Watt typical, 17.5 Watt maximum, remote end 16.5 Watt typical, 22.5 Watt maximum				
ENVIRONMENTAL SPECS					
OPERATING TEMPERATURE	-40° to 60°C (-40° to 140° Fahrenheit)				
STORAGE TEMPERATURE	-50° to 70°C (-58° to 158° Fahrenheit)				
HUMIDITY - IP RATING	100% relative humidity - IP67				
WIND LOADING	180 km/h (112.5 mph)				
PHYSICAL SPECS					
	DIMENSIONS			WEIGHT (Local / Remote end)	
PACKAGED (per unit)	QB-9100	14.56 x 13.0 x 7.87 in (370 x 331 x 200 mm)		9.92 lbs ( 4.5 kg) / 10.91 lbs (4.95 kg)	
	QB-9150	14.56 x 13.0 x 7.87 in (370 x 331 x 200 mm)		10.91 lbs (4.95 kg) / 11.90 lbs ( 5.4 kg)	
UNPACKAGED (per unit)	QB-9100	9.84 x 8.66 x 2.83 in (250 x 220 x 72 mm)		4.20 lbs (1.9 kg) / 5.07 lbs (2.3 kg)	
	QB-9150	12 x 12 x 3.40 in (305 x 305 x 85 mm)		5.30 lbs (2.4 kg) / 6.17 lbs (2.8 kg)	
SAFETY STANDARDS					
	UL 60950, CAN/CSA-C22.2 No. 60950, IEC 60950, EN 60950 (part -1 and -22)				
CERTIFICATIONS					
	USA: FCC 90Y + 15C + 15E (UNII 15.247); Canada: IC RSS 102 + RSS 111 + RSS 247; Europe: RED EN 301 489-1 + EN 301-489-17 + EN 300 328 + EN 301 893 + EN 302 502				
PACKAGE CONTENTS					
	<ul style="list-style-type: none"> <li>One ORINOCO® QB-9100 link with two (local) / four four (remote) N-type surge protected connectors</li> <li>Or One ORINOCO® QB-9150 link with integrated 22 dBi panel antenna (local and remote)</li> <li>plus Two N-type surge protected connectors (remote only)</li> <li>Two power injector and country specific power cord</li> <li>Two Connector weatherproofing kit (Includes all recommended weatherproofing material)</li> </ul>		<ul style="list-style-type: none"> <li>Two 2.4 GHz, 5 dBi omni antennas</li> <li>Two Grounding kit</li> <li>One Antenna alignment (RJ11) dongle</li> <li>One Quick Installation Guide</li> <li>Two Wall / Pole mounting kit</li> </ul>		
MTBF and WARRANTY					
	>250 000 hours, 2-year; ServPak Extended Support available.				